

# SP600S

## Optimizer



### MORE PRODUCTION

- Up to 30 % increased power generation
- Overcome potential losses on a module level with Shade-Proof technology



### FLEXIBLE DESIGN AND EASY TO INSTALL

- Patented structure to save installation time up to 45%
- Optimize rooftops with different orientations and tilt angles to increase solar system capacity



### SAFE AND RELIABLE

- Rapid shutdown to 30V within 20 seconds
- IP68 protection and C5 anti-corrosion



### EFFICIENT O&M

- Rapid data refresh in 10 seconds
- Module-level IV scanning and diagnosis \*

NEW



Type designation	SP600S
<b>Input</b>	
Rated input power	600 W
Max. input voltage	80 V
MPPT voltage range	8 V - 80 V
Max. DC short-circuit current ( I <sub>sc</sub> )	20 A
Overvoltage category	II
<b>Output</b>	
Max. output voltage	80 V
Max. output current	16 A
Bypass working mode	Yes
Safety output voltage per optimizer	1 V
<b>Efficiency</b>	
Max. efficiency	99.5 %
Weighted efficiency	99 %
<b>General Data</b>	
Dimensions ( W*H*D )	86 mm * 108 mm * 25 mm
Weight ( including cables )	0.5 kg
Degree of protection	IP 68
Allowable relative humidity range ( non-condensing )	0 % - 100 %
Operating ambient temperature range	-40 °C - 85 °C
Max. operating altitude	4000 m
Mounting Method	push-in and bolt installation
Communication	PLC (< 300 m )
Input / output connector	MC4 or MC4 Compatible
Input Wire Length	150 mm ( PV+ ) / 150mm ( PV- ) 150 mm ( PV+ ) / 900mm ( PV- ) ( Optional )
Output Wire Length	1200 mm
Standard compliance	IEC61000-6-2, IEC61000-6-3, IEC62109-1 ( class II safety )
Compatible products **	SG2.0 / 2.5 / 3.0RS-S ** SG3.0 / 3.6 / 4.0 / 5.0 / 6.0RS ** SH3.0 / 3.6 / 4.0 / 5.0 / 6.0RS ** SG5.0 / 6.0 / 8.0 / 10 / 12 / 15 / 17 / 20RT-P2 SG25 / 30 / 33 / 36 / 40 / 50CX-P2**

\* Currently 4 kinds of module-level diagnosis are available.

\*\* Please consult Sungrow before placing an order on optimizers and compatible inverters.

