

## PULSAR PLUS

<b>GENERAL SPECIFICATIONS</b>	
Charger	AC
Color	White or Black
Connector type	Type 1 or Type 2
Charging mode	Mode 3
Dimensions	166x163x82 mm (without cable)
Weight	1 kg (without cable)
Cable Length	5 m (7m optional)
Grounding Protection	Built-In Grounding (for the 7,4kW version)
<b>ELECTRICAL SPECIFICATIONS</b>	
Maximum Charging Power	7,4 kW (1Phase) / 22 kW (3Phase)
Rated Voltage AC $\pm$ 10%	220 V to 240 V (7,4kW) 400 V (11kW and 22kW)
DC Voltage range	-
Rated Current	32 A (7,4 kW - 1Phase) 16 A (11 kW - 3Phase) 32 A (22 kW - 3Phase)
Cable Section	5x10mm <sup>2</sup>
Configurable Current	from 6 A to rated current
Protection Rating	IP54 / IK08
Residual Current Detection	DC 6 mA
<b>CONNECTIVITY &amp; USER INTERFACE</b>	
Connectivity	Wi-Fi / Bluetooth
User Identification	myWallbox app
User Interface	myWallbox app & portal
Charger Status Information	RGB LED / myWallbox app & portal
Included Features	Power Sharing
Optional Features	Power Boost / Dynamic Power Sharing / MID Meter
Communication Protocol	myWallbox / OCPP 1.6j