



BV LCIE  
CHINA  
Number

N°2066AS07AVSV36001

## ATTESTATION of conformity with European Directives

*Product:* PV inverter (Grid-tied photovoltaic inverter)  
*Reference:* S700, S1000, S1500, S2000, S2500, S3000, S3300  
*Issued to:* Maitian Energy Co., Ltd  
*Address:* Room A203, Building C, No 205, Binghai Six Road, New Airport Industry Area, Longwan District, Wenzhou, Zhejiang Province  
*Manufacturer:* Maitian Energy Co., Ltd  
*Technical characteristics:* See below table

The submitted sample of the above equipment has been tested for **CE** marking according to following European Directive and following standards:

### Low Voltage Directive 2014/35/EU

Standards	Report number	Report date
EN 62109-1:2010 EN62109-2 :2011	AVSV-ESH-P20060323-1 AVSV-ESH-P20060323-2	2020-07-08

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product  
The **CE** marking may be affixed if all relevant and effective European Directives with **CE** marking applicable

Shanghai (P.R. China), July 15<sup>th</sup>, 2020.



Harvey Wang  
Product Line Manager



This document shall not be reproduced, except in full, without the written approval of BV LCIE China.  
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA  
必维欧亚电气技术咨询服务(上海)有限公司

Building 4, No. 518, Xin Zhuan Road,  
CaoHejing Songjiang High-Tech Park,  
Shanghai P.R.C (201612)

Tel: +86 21 6195 7000  
Fax: +86 21 6195 7001  
Email: [contact@cn.bureauveritas.com](mailto:contact@cn.bureauveritas.com)



**L C I E**

BV LCIE  
CHINA  
Number

N°2066AS07AVSV36001

<b>Model / Type</b> .....	S700	S1000	S1500
MPP DC voltage range [V] .....	50-500		
Max. Input DC voltage [V] .....	500		
Max. Input DC current [A].....	12,5		
Output AC voltage [V] .....	220/230/240V, 50/60Hz		
Max. Output AC current [A] .....	3,5	4,8	7,2
Rated output power [VA] .....	700	1000	1500

<b>Model / Type</b> .....	S2000	S2500	S3000	S3300
MPP DC voltage range [V] .....	50-500	50-550		
Max. Input DC voltage [V] .....	500	550		
Max. Input DC current [A].....	12,5			
Output AC voltage [V] .....	220/230/240V, 50/60Hz			
Max. output AC current [A].....	9,6	12,0	14,3	14,3
Rated output power [VA] .....	2000	2500	3000	3300

Shanghai (P.R. China), ), July 15<sup>th</sup>, 2020.



This document shall not be reproduced, except in full, without the written approval of BV LCIE China.  
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA  
必维欧亚电气技术咨询服务(上海)有限公司

Building 4, No. 518, Xin Zhuan Road,  
CaoHejing Songjiang High-Tech Park,  
Shanghai P.R.C (201612)

Tel: +86 21 6195 7000  
Fax: +86 21 6195 7001  
Email: [contact@cn.bureauveritas.com](mailto:contact@cn.bureauveritas.com)