

# Three Phase Inverter for the 277/480V Grid

SE40K



INVERTERS

## Specifically designed to work with power optimizers

- Fixed voltage inverter for superior efficiency (98.1%) and longer strings
- Quick and easy inverter commissioning directly from a smartphone using the SolarEdge SetApp
- Small, lightest in its class, and easy to install
- Integrated type 2 DC Surge Protection, to better with stand lightning events
- Optional RS485 and type 2 AC Surge Protection
- Advanced safety features - integrated arc fault protection and optional rapid shutdown
- Built-in module-level monitoring with Ethernet, wireless or cellular communication for full system visibility
- Smart Energy Management control
- IP65 Outdoor and indoor installation
- Optional integrated DC Safety Unit eliminates the need for external DC isolators
- Future-ready for SolarEdge energy storage evolution

# / Three Phase Inverter for the 277/480V Grid

## SE40K

Applicable to inverters with part numbers	SE40K	
	SEXXX-XXX8XXXX	
<b>OUTPUT</b>		
Rated AC Power Output	40000	W
Maximum apparent AC Output Power	40000	VA
AC Output Voltage - Line to Line / Line to Neutral (Nominal)	480 / 277	Vac
AC Output Voltage - Line to Neutral Range	244-305	Vac
AC Frequency	50/60 ± 5%	Hz
Maximum Continuous Output Current (per Phase)	48.25	Aac
AC Output Line Connections	3W + PE, 4W + PE	
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes	
Total Harmonic Distortion	≤ 3	%
Power Factor Range	0 - 1 leading, lagging	
<b>INPUT</b>		
Maximum DC Power (Module STC)	60000	W
Transformer-less, Ungrounded	Yes	
Maximum Input Voltage DC to Gnd	1000	Vdc
Maximum Input Voltage DC+ to DC-	1000	Vdc
Nominal Input Voltage DC+ to DC-	850	Vdc
Maximum Input Current	48.25	Adc
Reverse-Polarity Protection	Yes	
Ground-Fault Isolation Detection	150kΩ Sensitivity <sup>(1)</sup>	
Maximum Inverter Efficiency	98.1	%
European Weighted Efficiency	98	%
Nighttime Power Consumption	< 4	W
<b>ADDITIONAL FEATURES</b>		
Supported Communication Interfaces	2 x RS485, Ethernet, Wi-Fi (requires an antenna), Cellular (optional)	
Smart Energy Management	Export Limitation	
Inverter Commissioning	With the SetApp mobile application using built in Wi-Fi access point for local connection	
Arc Fault Protection	Integrated, User Configurable (According to UL1699B)	
Rapid Shutdown	Optional <sup>(2)</sup> (Automatic upon AC Grid Disconnect)	
RS485 Surge Protection	Optional	
DC Surge Protection	Type II, field replaceable, Integrated	
AC Surge Protection	Type II, field replaceable, Optional	
<b>DC SAFETY UNIT (OPTIONAL)</b>		
2-pole Disconnection	1000V / 48.25A	
DC Fuses (Single Pole)	25A ,Optional	
Compliance	UTE-C15-712-1	
<b>STANDARD COMPLIANCE</b>		
Safety	IEC-62103 (EN50178), IEC-62109, AS3100	
Grid Connection Standards <sup>(3)</sup>	BDEW, CEI-016	
Emissions	IEC61000-6-2, IEC61000-6-3 Class A, IEC61000-3-11, IEC61000-3-12	
RoHS	Yes	
<b>INSTALLATION SPECIFICATIONS</b>		
AC Output Gland Diameter / Line cross section / PE cross section	Cable diameter 19-28 mm / 4 – 16 mm <sup>2</sup> / 4 – 16 mm <sup>2</sup>	
Inverter with Safety Unit AC Output Gland Diameter / Line crosssection / PE cross section	Cable diameter 19-28 mm / 6 16 mm <sup>2</sup> / 6 16 mm <sup>2</sup>	
DC Input <sup>(4)(5)</sup>	4 MC4 pairs	
DC Input with Safety Unit <sup>(4)(5)</sup>	4 MC4 pairs	
	4 Strings: Gland: Cable outer diameter, 5 - 10 mm / Wire cross section 2.5 - 16mm <sup>2</sup>	
	Single pair: Gland: Cable outer diameter, 9 - 16 mm / Wire cross section 6 - 35mm <sup>2</sup>	
Dimensions (HxWxD)	550 x 317 x 273	
Dimensions with Safety Unit (HxWxD)	836 x 317 x 300 (DC MC4); 819 x 317 x 300 (DC Gland)	
Weight	32	
Weight with Safety Unit	36.5	
Operating Temperature Range	-40 to +60	
Cooling	Fan (user replaceable)	
Noise	< 62	
Protection Rating	IP65	
Mounting	Bracket Provided	

(1) Where permitted by local regulations

(2) Inverter with rapid shutdown part number: SEXXX-xxRxxxxxxx

(3) For all standards refer to Certifications category in Downloads page: <http://www.solaredge.com/groups/support/downloads>

(4) Only MC4 connectors manufactured by Stäubli are approved for use

(5) DC input available with MC4 or Gland connectors under the inverter part number. For more information, contact SolarEdge