

SolarEdge Home Wave Inverter

Single Phase, for Europe

SE2200H, SE3000H, SE3500H, SE3680H,
SE4000H, SE5000H, SE6000H

INVERTERS



Optimized installation with HD-Wave technology

- Specifically designed to work with SolarEdge Power Optimizers
- Industry leading efficiency with 200% DC oversizing
- Quick and easy inverter commissioning directly from a smartphone using the SolarEdge SetApp
- Seamless wireless connectivity with system devices such as the SolarEdge Home Battery, via optional SolarEdge Home Network platform
- Extremely compact, lightweight and easy to install
- Built-in module-level monitoring
- Suitable for outdoor and indoor installation
- Fixed voltage inverter for longer strings
- Advanced safety feature - integrated arc fault protection

SolarEdge Home Wave Inverter

Single Phase, for Europe

SE2200H, SE3000H, SE3500H, SE3680H, SE4000H, SE5000H, SE6000H

SE2200H SE3000H SE3500H SE3680H SE4000H SE5000H SE6000H

APPLICABLE TO INVERTERS WITH PART NUMBER

SEXXXXH-XXXXXBXXX4

OUTPUT

Rated AC Power Output	2200	3000	3500	3680	4000	5000 ⁽¹⁾	6000	VA
Maximum AC Power Output	2200	3000	3500	3680	4000	5000 ⁽¹⁾	6000	VA
AC Output Voltage (Nominal)	220/230							Vac
AC Output Voltage Range	184 - 264.5							Vac
AC Frequency (Nominal)	50/60 ± 5							Hz
Maximum Continuous Output Current	10	14	16	16	18.5	23	27.5	A
Total Harmonic Distortion (THD)	<3							%
Power Factor	1, adjustable -0.9 to 0.9							
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes							

INPUT

Maximum DC Power	4400	6000	7000	7360	8000	10000 ⁽²⁾	12000	W
Transformer-less, Ungrounded	Yes							
Maximum Input Voltage	480							Vdc
Nominal DC Input Voltage	380							Vdc
Maximum Input Current	6.5	9	10	10.5	11.5	13.5	16.5	Adc
Reverse-Polarity Protection	Yes							
Ground-Fault Isolation Detection	600kΩ Sensitivity per Unit							
Maximum Inverter Efficiency	99.2							%
European Weighted Efficiency	98.3	98.8				99		%
Nighttime Power Consumption	< 2.5							W

ADDITIONAL FEATURES

Supported Communication Interfaces	RS485, Ethernet, Wi-Fi (optional), wireless SolarEdge Home Network (optional) ⁽³⁾ , Cellular (optional), ZigBee (optional)
Smart Energy Management	Export Limitation
Inverter Commissioning	With the SetApp mobile application using built in Wi-Fi station for local connection
Arc Fault Protection	Integrated, User Configurable (According to UL1699B)

STANDARD COMPLIANCE

Safety	IEC-62109-1/2
Grid Connection Standards	IEC61727, IEC62116, EN 50438, VDE-AR-N-4105, VDE 0126-1-1, UTE_C_15-712, G98, G99, CEI-021, ÖNORM, TF3.2.1, C10-11, NRS 097-2-1
Electromagnetic Compatibility (EMC)	EN/IEC 61000-6-1, EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN/IEC 61000-6-4, EN 55011, FCC Part 15, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN/IEC 61000-3-11, EN/IEC 61000-3-12

INSTALLATION SPECIFICATIONS

AC Output - Supported Cable Diameter	9-16							mm
AC - Supported Wire Cross Section	1-13							mm ²
DC Input	1 x MC4			2 x MC4 pair				
Dimensions (H x W x D)	280 x 370 x 142							mm
Noise	< 25							dBA
Weight	7.8			9		10.6		kg
Cooling	Natural Convection							
Operating Temperature Range	-40 to +60 ⁽⁴⁾							°C
Protection Rating	IP65 — Outdoor and Indoor							

(1) 4600VA in Germany

(2) 7130VA in Germany

(3) For more information, refer to: <https://www.solaredge.com/sites/default/files/se-energy-net-plug-in-datasheet.pdf>

(4) Full power up to at least 50°C / 122°F. For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note.pdf>